

IIB-1553-MMA

The IIB-1553-MMA is an intelligent interface card providing full MIL-STD-1553 test, simulation and bus analysis capability for the M-Module standard, with 1553A, 1553B, McAir and STANAG 3838 variants in one card. The IIB-1553-MMA supports concurrent Bus Controller (BC) and up to 31 Remote Terminals (RT) with Bus Monitor (BM). An additional stand-alone Chronological Bus Monitor (CBM) facility is also provided, with comprehensive multi-level triggering capability. Full error injection capability is provided in BC and RT modes, with full error detection in BC, RT, BM and CBM modes. The unit provides a dual redundant 1553 interface. 2 Mbytes of dual ported RAM are provided. The board is supplied with C drivers in source code and Windows menu driven software as standard.

SPECIFICATIONS

General Specifications

- MIL-STD-1553A/B, STANAG 3838 compatible
- McAir compatible
- 2 Mbytes Dual Port RAM (all modes)
- BIT and diagnostics
- All set-ups programmable in real time
- Programmable for Direct or TX coupling
- Programmable TX amplitude
- Full error injection (BC & RT)
- Full error detection (all modes)

Bus Controller

Programmable inter-message delay
Programmable RT response time
Programmable Frame frequency
Programmable message sequencing
Messages and data changeable in real time
Acyclic message insertion
BC-RT, RT-BC, RT-RT, mode code, broadcast
Multiple data buffering, all transmitted and received messages
Full error injection / detection

Remote Terminal

Multiple RT simulation (up to 31 RT's)
All sub-addresses selectable
Selectable Broadcast mode
Programmable Mode Code sub-address
Programmable Status word
Programmable RT response time
Message time tagging (32 bit @ 500 nSec)
All active RT tables changeable in real time
Data and Status words changeable in real time

Bus Monitor

All data buffers monitored
All data time tagged (32 bit @ 10 uSec resolution)
All data available for analysis

Chronological Bus Monitor

Programmable conditional triggers and masks
Message time tagging (32 bit @500 nSec resolution)
Store all, store only, store after modes
Full error detection capability

Host Interface

M-Module: 16-bit data
Memory Space: 2 Mbytes
Interrupts: ROAK

Power

Total > 15 Watts
+5v +/- 5% 600 mAmps
+12V +/- 5% 160 mAmps

Physical Characteristics

Dimensions 148mm x 52mm
Weight 100 grams

Environmental

Operating Temp. 0 – 50°C
Storage Temp. -20 – 70°C
Humidity 5% – 95% Noncondensing
MTBF (MIL 217F) 104,817 hrs at 25°C (Gb).

Software Support

C drivers in source code
Windows menu software (WinNT, Win95)

Order Codes

1U10994G01 MIL-STD-1553 for MMA

Contact Information

Technical & Sales queries: support@western-av.com
Phone: 353-61-472233
Fax: 353-61-471675
Web-site: <http://www.western-av.com>